WHAT IS CLAIMED IS:

1   1.   A   method   of   facilitating   compressed   message
2 communication   between   a   first   communication   entity   and   a
3 second communication entity, said method comprising the steps
4 of:

5   compressing,   at   said   first   communication   entity,   a
6 portion   of   a   first   communication   message   using   a   first
7 dictionary   to   produce   a   first   compressed   communication
8 message;

9   transmitting said first compressed communication message
10 to said second communication entity;

11   receiving   said   first   compressed   communication   message
12 at said second communication entity;

13   decompressing, at said second communication entity, said
14 first   compressed   communication   message   using   a   second
15 dictionary to reproduce said first communication message; and

16   adding said portion of said first communication message
17 to said second dictionary.

28

1   2.   The   method   of   claim   1,   said   method further

2   comprising the steps of:

3   compressing,   at   said   second   communication   entity,   a

4   portion of a second communication message using said second

5   dictionary   to   produce   a   second   compressed   communication

6   message;

7   transmitting   said   second   compressed   communication

8   message to said first communication entity;

9   receiving said second compressed communication message

10   at said first communication entity;

11   adding said portion of said first communication message

12   to said first dictionary; and

13   decompressing,   at   said   first   communication   entity,   said

14   second   compressed   communication   message   using   said   first

15   dictionary to reproduce said second communication message.

1   3.   The   method   of   claim   2,   said   method further

2   comprising the step of:

3   adding said portion of said second communication message

4   to said first dictionary.

29

1   4.   The method of claim 2, wherein said step of

2   transmitting said first compressed communication message and

3   said   step   of   transmitting   said   second   compressed

4   communication message comprises transmitting over a wireless

5   interface.

1   5.   The method of claim 3, said method further

2   comprising the steps of:

3   compressing, at said first communication entity, a

4   portion of a third communication message using said first

5   dictionary to produce a third compressed communication

6   message;

7   transmitting said third compressed communication message

8   to said second communication entity;

9   receiving said third compressed communication message

10   at said second communication entity;

11   decompressing, at said second communication entity, said

12   third compressed communication message using said second

13   dictionary to reproduce said third communication message; and

14   adding said portion of said second communication message

15   to said second dictionary.

1   6.   The method of claim 1, said method further

2   comprising the steps of:

3   compressing, at said second communication entity, a

4   portion of a second communication message using a third

5   dictionary to produce a second compressed communication

6   message;

7   transmitting said second compressed communication

8   message to said first communication entity;

9   adding said portion of said second communication message

10   to said third dictionary;

11   receiving said second compressed communication message

12   at said first communication entity;

13   decompressing, at said first communication entity, said

14   second compressed communication message using a fourth

15   dictionary to reproduce said second communication message;

16   and

31

17   adding said portion of said second communication message

18   to said fourth dictionary.

32

1   7.   A communications device for facilitating compressed

2   message communication, said communications device comprising:

3   a receiver unit;

4   a transmitter unit;

5   a processor; and

6   memory having stored therein at least one dictionary and

7   program software having instructions which, when executed by

8   the processor, causes the communications device to:

9   receive, by said receiver unit, a first

10 communication message from another communications device,

11 said communication message having a compressed portion

12 therein;

13   decompress, using said at least one dictionary,

14 said compressed portion of said first communication message;

15 and

16   add said compressed portion to said at least one

17 dictionary.

1   8.   The communications device of claim 7, wherein the

2   program software further includes instructions which, when

3   executed by the processor, causes the communications device

4   to:

5   compress, using said at least one dictionary, a

6   portion of a second communication message to obtain a

7   compressed portion thereof;

8   transmit, by said transmitter unit, said second

9   communication message having the compressed portion to said

10   another communications device; and

11   add, to said at least one dictionary, the

12   compressed portion of said second communication message upon

13   reception, by said receiver unit, of a third communication

14   message by said another communications device.

1   9.   The communications device of claim 7, wherein said

2   communications device comprises a mobile terminal.

1   10.   The communications device of claim 7, wherein said

2   communications device comprises a base station.

34

35

1   11. A communications device, comprising:

2   a receiver unit;

3   a transmitter unit;

4   a processor; and

5   memory having stored therein at least one dictionary and

6   program software having instructions which, when executed by

7   the processor, causes the communications device to:

8   compress, using said at least one dictionary, a

9   portion of a communication message to obtain a compressed

10   portion thereof;

11   transmit, by said transmitter unit, said

12   communication message having the compressed portion to

13   another communications device; and

14   add, to said at least one dictionary, the

15   compressed portion of said communication message upon

16   reception, by said receiver unit, of a second communication

17   message by said another communications device.

1   12. The communications device of claim 11, wherein said

2   at least one dictionary comprises a first dictionary for

3   storing said compressed portion and a second dictionary for

4   storing at least one compressed portion of messages received

5   by said receiver unit.

1   13. The communications device of claim 11, wherein said

2   communications device comprises a mobile terminal.

1   14. The communications device of claim 11, wherein said

2   communications device comprises a base station.

1   15. The communications device of claim 11, wherein said

2   another communications device comprises a mobile terminal.

1   16. The communications device of claim 11, wherein said

2   another communications device comprises a base station.

37

1   17. A communication system for facilitating compressed

2   message communication, said communication system comprising:

3   a first communication entity for sending a first

4   communication message, said first communication entity

5   comprising:

6   a first dictionary;

7   a first compressor in communication with said first

8   dictionary, said first compressor using said first

9   dictionary to compress a portion of a first communication

10   message to produce a first compressed communication message;

11   and

12   a first transmitting means in communication with

13   said first compressor, said first transmitting means

14   transmitting said first compressed communication message; and

15   a second communication entity, in communication with

16   said first communication entity, for receiving said first

17   compressed communication message, said second communication

18   entity comprising:

19   a first receiving means for receiving said first

20   compressed communication message;

38

21   a second dictionary;

22   a first decompressor, in communication with said

23   first receiving means and said second dictionary, said first

24   decompressor   decompressing,   said   first   compressed

25   communication   message   using   said   second   dictionary   to

26   reproduce said first communication   message; and

27   a first updating means, in communication with said

28   decompressor and said second dictionary, said first updating

29   means   updating   said   portion   of   said   first   communication

30   message to said second dictionary.

1   18.   The communication system of claim 17, said second

2   communication entity further comprising:

3   a second compressor, in communication with said second

4   dictionary, said second compressor compressing a portion of

5   a second communication message using said second dictionary

6   to produce a second compressed communication message; and

7   a second transmitting means, in communication with said

8   second   compressor,   said   second   transmitting   means

39

9   transmitting said second compressed communication message to

10   said first communication entity.

1   19. The communication system of claim 18, said first

2   communication entity further comprising:

3   a second receiving means for receiving said second

4   compressed communication message;

5   a second decompressor, in communication with said second

6   receiving means and said first dictionary, said second

7   decompressor decompressing said second compressed

8   communication message using said first dictionary to

9   reproduce said second communication message; and

10   a second updating means, in communication with said

11   decompressor and said first dictionary, said second updating

12   means updating a first one of said portion of said first

13   communication message and said portion of said second

14   communication message to said first dictionary.